




www.oemmespa.com



**RU**

**AUTOMATIC UNLOADING ROLLER CONVEYORS  
FOR THERMAL BREAK ASSEMBLY EQUIPMENT**





**RU 826** Unloading roller conveyor with chutes



**Technical details**

- Idle roller conveyor with polizene rollers Ø50 mm – step 450 mm
- Length = 6500 mm
- Motor powered rubber roller driven by a pneumatic cylinder to facilitate the coming out of the bar
- Orthogonal pneumatic pusher with 3 pivoting arms, provided with rubber roll in the contact point with the bar
- 3 polizene chutes, length 3000 mm, provided with hinges to fold the roller conveyor when it is not used
- External wire fence protection, height = 2000 mm, with entrance gate equipped with safety micro
- Side supports for polyamide bars, fixed to the external wire fence protection
- Electric system with box on board of machinery and control console
- Overall dimensions: 9960 mm (a) x 3500 mm (b) x 2000 mm (c)
- Weight: 550 Kg

**RU 834** Unloading palletizer roller conveyor




- Idle roller conveyor with polizene rollers Ø50 mm – step 450 mm
- Length = 6500 mm
- Motor powered rubber roller driven by a pneumatic cylinder to facilitate the coming out of the bar
- Orthogonal pneumatic pusher with 3 pivoting arms, provided with rubber roll in the contact point with the bar
- 4 polizene ledges length 1000 mm for bars accumulation (max. capacity 700 mm)
- Side pneumatic jogger for alignment of the accumulated bars, before collection
- Collection reed equipped with 2 motor powered trolleys and 4 forks (unloading height controlled by a sensor)
- Accumulation max height = 500 mm plus last layer
- External wire fence protection, height = 2000 mm, with entrance gate equipped with safety micro
- Side supports for polyamide bars, fixed to the external wire fence protection
- Electric system with box on board of machinery and control console
- Overall dimensions: 9960 mm (a) x 3540 mm (b) x 2000 mm (c)
- Weight: 1250 Kg

**RU 835** Unloading belt roller conveyor



- Motor powered roller conveyor with polizene rollers Ø 50 mm – step 200 mm and photocell for bar stop
- Length = 7000 mm
- Horizontal translator with step by step operation, consisting of 4 load chains provided with pushers/spacers
- 2 bar accumulation tanks length 2030 mm each, consisting of 4 motor driven load chains with step by step device
- Automatic or manual unloading of the first tank
- Manual collection from the top with feed controlled by the operator and stop by the photocell
- External wire fence protection, height = 2000 mm, with entrance gate equipped with safety micro
- Electric system with box on board of machinery and control console
- Overall dimensions: 9000 mm (a) x 5400 mm (b) x 2000 mm (c)
- Weight: 1400 Kg



**Export Department**  
Via F. L. Ferrari, 23  
44100 FERRARA - ITALY  
Tel. +39.0532.777418  
Fax +39.0532.777477  
sales@oemmespa.com

**Sales office Italy**  
Via Cavallotti, 16  
42010 REGGIO EMILIA - ITALY  
Tel. 0522.271275  
Fax 0522.923879  
vendite@oemmespa.com

**Head office and Production**  
Via F. L. Ferrari, 23  
44100 FERRARA - ITALY  
Tel. 0532.777411  
Fax 0532.777444  
info@oemmespa.com