



RU 800L - Loading roller conveyor



Technical features

- Aluminum structure equipped with two support feet
- PVC bar sliding rollers
- Ingombro: versione 4 m: 4430 mm (a) x 450 mm (b) x 1060 mm (c)
- versione 3 m: 3430 mm (a) x 450 mm (b) x 1060 mm (c)
- Weight: 50 kg (4 m version) / 44 kg (3 m version)

Technical Commercial Data Sheet

Roller conveyor RU 800 L - RU 801U - RU 802UD

RU 801U - Manual unloading roller conveyor



Technical features

Aluminum structure equipped with two support feet

PVC bar sliding rollers

Ingombro: versione 4 m: 4430 mm (a) x 450 mm (b) x 1060 mm (c)

versione 3 m: 3430 mm (a) x 450 mm (b) x 1060 mm (c)

Weight: 50 kg (4 m version) / 44 kg (3 m version)

RU 802UD - Displayed unloading roller conveyor



Technical features

Useful cutting: 4000 mm (4 m version) – 3000 mm (3 m version)

Manual stop positioning via handwheel with pneumatic locking device

Reading of the beaten quota on the decimal display

Magnetic strip sensor for detecting the hit height

Aluminum structure equipped with two support feet

PVC bar sliding rollers

Ingombro: versione 4 m: 4630 mm (a) x 500 mm (b) x 1270 mm (c)

versione 3 m: 3630 mm (a) x 500 mm (b) x 1270 mm (c)

Weight: 63 kg (4 m version) / 57 kg (3 m version)